

96PR-220-USE-SB

180 dpi POS Printer, 2.83", 9 ips,
USB/Serial/Ethernet



Features

- Energy Star qualified for power efficiency
- ESC/POS command compatible
- Auto cutter
- Supports various drivers and SDK: Windows, Win CE, Linux, iOS, and Android
- Supports wall mount installation

Specifications

Printing	Method	Direct Thermal
	Speed	Max. 220mm (8.66 in.) /sec
	Width	72 mm (2.83 in.) 512 dots/line
	Resolution	180 dpi
Paper	Type	Thermal Receipt Paper / Linerless(Optional)
	Width	50 ~ 82.5 mm (1.97 ~ 3.25 in.)
	Thickness	0.06 ~ 0.09 mm (0.002 ~ 0.003 in.)
	Roll Diameter	Max. Ø80.0 mm (3.15 in.)
	Roll Core Inner	12.5 ± 0.5 mm (0.49 ± 0.02 in.)
Reliability	TPH Life	160 km (99.41 mile)
	MCCBF	60,000,000 Lines
Auto Cutter		1,800,000cuts(Guillotine)
Sensor	Standard	Paper End, Paper Low, Cover Open
	Option	Black Mark
Interface		USB (B type) + Ethernet + Serial Built-in
Emulation		ESC/POS Command Compatible
Driver		Windows Driver(10, 2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Windows CE & Mobile Driver & SDK(CE 4.2 -, Mobile 5.0 -), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1 -) SDK, Windows SDK
Power	Type	External SMPS
	AC	100 ~ 240V _{AC} 50/60 Hz
	DC	24V _{DC} / 1.75A
Temperature	Operation	0 ~ 45°C (32 ~ 113°F)
	Storage	-20 ~ 60°C (-4 ~ 140°F)
Dimension (W x D x H)		152 x 204 x 150 mm (5.98 x 8.03 x 5.9 in.)
Weight		1.7 kg (3.74 lb.)
Color		Cool grey, Ivory

Ordering Information

Part Number	Description
96PR-220-USE-SB	Desktop Direct Thermal Receipt Printer, 180dpi, USB/Serial/Ethernet, US power cord
96PR-220-USE-SBA	Desktop Direct Thermal Receipt Printer, 180dpi, USB/Serial/Ethernet, AU power cord
96PR-220-USE-SBE	Desktop Direct Thermal Receipt Printer, 180dpi, USB/Serial/Ethernet, EU power cord

Packing List

- Adapter
- AC cord (1.5m)
- CD (manual, drivers, utility, etc.)
- Roll paper