# **ACP-4320**

### **Quiet 4U Rackmount Chassis with Dual Hot-Swap SATA HDD Trays**



#### **Features**

- Supports either an ATX motherboard or a PICMG backplane with up to 15 slots
- Supports dual SATA hot-swap HDD trays
- LED indicators and alarm notification for system fault detection
- Low noise system fans
- Built-in Intelligent System Module enabling whole system fan control and remote manageability

# **Quiet Specifications**

C € FCC


Driver Bay		External	Internal	
	5.25"	2	-	
	3.5"	1 SATA Tray	-	
	Hot Swap	2 (compatible with 3.5" or 2.5" devices)		
Cooling	Fan	1(12 cm/74 CFM) + 1 (6cm / 28 CFM)		
	Air Filter	Yes		
	Smart Fan	System fan speed referring to chassis thermal sensor, (Available with selected Advantech MBs/CPU cards)	or CPU temperature	
Front I/O Interface	USB 2.0	2		
Miscellaneous	LED Indicators	Power, HDD, temperature, fan, LAN1 and LAN2		
	Rear Panel	Backplane version: One 9-pin D-Sub opening		
	Motherboard version: Five 9-pin D-Sub opening and		one 25-pin D-sub opening	
Intelligent System Module Remote Monitoring	CPU/System fan speed, CPU/system temperature, motherboard voltage (Only selected Advantech MBs/CPU cards with WISE-PaaS/RMM installed can fully enable these functions, check with Advantech local rep. for			
	detailed information.)	Operating	Non Operating	
Environment	Tomporatura	Operating	Non-Operating	
	Temperature	0 ~ 40 °C (32 ~ 104 °F)	- 20 ~ 60 °C (-4 ~ 140 °F)	
	Humidity	10 ~ 85% @ 40 °C , non-condensing	10 ~ 95% @ 40 °C, non-condensing	
	Vibtration (5 ~ 500 Hz)	1 Grms	2 G	
	Shock	10G ( with 11 ms duration, half sine wave )		
Physical Characterisitics	Dimension (W x H X D)	482 x 177 x 479 mm (19" x 7.0" x 18.9")		
	Weight	17.6 kg (38.7lb)		

### **Front View**

# System reset button Alarm reset button Dual USB ports Two 5.25" drive bays Two SATA HDD trays

### **Inside View**





# **Ordering Information**

Part number	Power supply	Wattage	Switch type			
Backplane version						
ACP-4320BP-25BE	PS8-250ATX-ZE	250W	ATX			
ACP-4320BP-40BE	PS8-400ATX-ZE	400W	ATX			
ACP-4320BP-50BE	PS8-500ATX-ZE	500W	ATX			
Motherboard version						
ACP-4320MB-25BE	PS8-250ATX-ZE	250W	ATX			
ACP-4320MB-40BE	PS8-400ATX-ZE	400W	ATX			
ACP-4320MB-50BE	PS8-500ATX-ZE	500W	ATX			

## **Optional Accessories**

Part Number	Description
IPC-DT-3120E	Mobile rack for converting a 3.5" drive bay to dual 2.5" SATA HDD trays
IPC-DT-5230E	Mobile rack for converting dual 5.25" drive bays to three 3.5" SATA HDD trays
1700007351	M Cable SATA 7P/SATA 7P 40CM C=R 90/180

When choosing ASMB-781, ASMB-782, ASMB-820, ASMB-823 for system mother board, 2pcs right-angle SATA cable (PN: 1700007351) are necessary for hot-swap driver bay.

## **Spare Parts**

Part Number	Description
1990001299	Fan filter 95 x 130 mm
1990001298	Door filter 150 x 68 mm