AIM-38 Extensions and Accessories

Extension Modules

Barcode Scanner (20°)

Barcode Scanner (70°)

LAN + COM Module

UHF RFID Reader









Part Number	AIM-P511A0	AIM-EXTO-0041	AIM-EXTO-0046	AIM-EXTO-0047 (EU) AIM-EXTO-0049 (US)
Color	Black	Black	Black	Black
Dimensions	130.2 x 38.7 x 27.8 mm (5.12 x 1.52 x 1.09 in)	130.2 x 38.7 x 32 mm (5.12 x 1.52 x 1.25 in)	130.2 x 70 x 29 mm (5.12 x 2.75 x 1.14 in)	130.2 x 63.6 x 65.9 mm (5.12 x 2.5 x2.59 in)
Weight	0.042 kg (0.092 lb)	0.042 kg (0.092 lb)	0.078 kg (0.171 lb)	0.08 kg (0.176 lb)
Feature	Sensor: 640 x 480 CMOS sensor Illumination & Aiming: White LED illumination/Red LED dot aimer Frame rate: 30 fps Field of view: Horizontal: 37.8°; Vertical: 28.8°	 Sensor: 640 x 480 CMOS sensor Illumination & Aiming: White LED illumination/Red LED dot aimer Frame rate: 30 fps Field of view: Horizontal: 37.8°; Vertical: 28.8° 	1 x 10/100 Ethernet port1 x COM port	 RFID output power: 25 watt RFID antenna type: Linear polarization Frequency: EU: 867 ~ 869MHz; US: 913 ~ 917 MHz Tag standard supported: EPC Class 2 Gen. 2/ ISO 18000-6C

Accessories

Hand Strap

Shoulder Strap



Battery with Meter







Active Stylus



Part Number	AIM-SRP0-0000	AIM-SRP0-0001	AIM-P704	AIM-BATO-0452
Color	Black	Black	Black	Black
Dimensions	240 x 20 mm (9.44 x 0.78 in)	380 x 135 x 20 mm (14.96 x 5.31 x 0.78 in)	140 x 9.7 mm (5.51 x 0.38 in)	120 x 87 x 7.5 mm (4.72 x 3.43 x 0.30 in)
Weight	0.022 kg (0.048 lb)	0.05 kg (0.11 lb)	0.02 kg (0.044 lb)	0.147 kg (0.324 lb)
Feature	 Synthetic leather w/ Elastic band Easily removed screw for rapid installation Extra protection against drop 	 Provide an easy way to carry on AIM-38 for retail industry Easily removed screw for rapid installation Extra protection against drop 	 Windows hardware certification approved Palm detection Pressure Detection 	 Suitable for retail industry to check the usage of each battery Easy to do battery swap, no need to wait for charging