


BAPL1-IL



Intel® Pentium N4200 / Atom Quad Core Mini-ITX

Features

- ▶ Supports Intel Pentium processor N4200
- ▶ Two 204-pin SO-DIMM up to 8 GB DDR3L 1866 MHz SDRAM
- ▶ Supports DP, HDMI, LVDS
- ▶ Supports 1 M.2 (key-M), 1 Mini-PCIe expansion slot, 4 COMs, 4 USB 3.0 & 2 USB 2.0, dual LAN
- ▶ Low profile design

Specifications

System

CPU	Supports Intel Pentium N4200 1.1GHz Quad Core Processor
BIOS	AMI 128Mb SPI Flash
System Chipset	SoC
I/O Chip	Nuvoton NCT6106D
Memory Type	Two 204-pin SODIMM sockets support up to 8GB DDR3L-1867 SDRAM
Watchdog Timer	Reset : 1 to 255 sec/min per step
Expansion	1 Mini-PCIe, 1 PCIe x1
Power Status	S0, S3, S4, S5
Wake up on LAN or Ring	LAN (WOL, PXE)
Smart Fan Control	Yes

I/O

MIO	1 LVDS, 2 USB2.0, 1 M.2, 1 MicroSD, 3 RS-232, 1 RS-232 with 5V/12V Power (WOL), 1 PS2 Combo, 2 SATA3, 2 Fan, 1 LPC, 1 8-bit GPIO, 1 DC_in
USB	4 USB3.0(rear), 2 USB2.0(internal)
GPIO	8-bit General Purpose I/O

Display

HDMI	Onboard, supports max resolution 3840 x 2160 @ 30Hz
DisplayPort	Onboard, supports DP 1.2 (4096x2160@60Hz)
LVDS	Onboard, dual channel 24-bit LVDS, max 1920 x 1200@60Hz

Audio

Audio Codec	Realtek ALC892, 5.1 Channel HD Audio
Audio Interface	Line-out, Mic-in, Front Audio Header

Ethernet

LAN 1	Realtek RTL8111G Gigabit LAN
LAN 2	Realtek RTL8111G Gigabit LAN

Back Panel I/O Port

1 DisplayPort
1 HDMI Port
4 USB 3.0 Port
1 Line-out, 1 Mic-in
1 DC-in Connector
2 LAN RJ45 Port

Internal I/O Connector

4 COM RS-232 Connector
2 SATA 3.0 Connector
1 SATA Power Connector
1 Front Panel Connector
1 Front Audio Connector
1 CPU Fan Connector
1 System Fan Connector
1 USB 2.0 Connector
1 M.2
1 Mini PCI-E Connector
1 Keyboard/ Mouse Connector
1 LVDS Connector
1 LVDS Backlight Connector
1 GPIO Connector

Power

Power Requirement	+12V (5A)
Power Type	12V DC-in
Power Connector	1 4-pin DC-in Power Connector, 1 4-pin ATX 12V Power Connector

Mechanical & Environmental

Operating Temperature	0°C to 60°C (32°F to 140°F)
Operating Humidity	95%@40°C (non-condensing), operating
Size (L x W)	6.69" x 6.69" (170 mm x 170 mm)
Weight	0.77 lbs (0.35 Kg)

Ordering Information

Part Number	Description
TBD	BAPL1-IL mini-ITX CRB for N4200