

Heavy Industrial RS-232 Isolated Repeater

Model BB-232OPDRI-PH

ADVANTECH

www.advantech.com



PRODUCT FEATURES

- Extends RS-232 data signals
- 2kV, three-way isolation (input/output/power)
- Data rate: 1.2 to 115.2 kbps
- Wide operating temperature: -40 to +85 °C
- Rugged IP30 metal case (panel or DIN rail mount)
- 10-48 VDC input power (power supply required, sold separately)

Model BB-232OPDRI-PH is a premium heavy industrial RS-232 isolated repeater. Designed for rugged industrial environments, it has passed some of the most exacting compliance tests in the industry. Meeting IEC 61850-3 and IEEE 1613 requirements, it is suitable for installation in electrical substations. These specifications are more stringent than NEMA TS1/TS2 transportation application requirements.

Powerful isolation on both data ports protects your equipment and data from damaging ground loops and surges. Additional isolation on power supply circuits adds a third degree of protection.

Packaged in a rugged IP30 metal case, this repeater operates in wide temperature extremes. The panel mount form factor with DIN rail mount option makes it easy to integrate into your control panel or other industrial equipment.

Installation and configuration is easy. Data is connected with a DB9 female connector (DCE) and a DB9 male connector (DTE).

Power is connected via terminal block that accepts 10 to 48 VDC from any external source. (Power supply required, not included, sold separately.)

ORDERING INFORMATION

| MODEL NUMBER | DESCRIPTION |
|----------------|---|
| BB-232OPDRI-PH | Heavy Industrial RS-232 Isolated Repeater |

ACCESSORIES – sold separately

| | |
|--------------|---|
| BB-MDR-40-24 | DIN rail mount power supply, 24 VDC, 1.7 A output power |
| BB-DRAD35 | DIN rail mounting kit, 35mm |
| BB-TBKT1 | Replacement Terminal Block - 2-position, 5.08mm, 8A, 30 |

All product specifications are subject to change without notice.
BB-232OPDRI-PH_2320ds

ADVANTECH

Advantech B+B SmartWorx, 707 Dayton Road, PO Box 1040 Ottawa, IL 61350 USA 1 (800)346-3119/Toll Free | orders@advantech-bb.com | support@advantech-bb.com

Heavy Industrial RS-232 Isolated Repeater

Model BB-232OPDRI-PH



SPECIFICATIONS

| SERIAL TECHNOLOGY | |
|----------------------------------|--|
| Serial Connector | DB9 F (DCE), DB9 M (DTE) |
| Data Rate | Up to 115.2 Kbps |
| Isolation | 2 KV RMS, 1 minute |
| POWER | |
| Source | External (required, not included, sold separately) |
| Power Connector | 2-position removable terminal block |
| Input Voltage | 10 to 48 VDC (56 VDC, maximum) |
| Power Consumption | 0.55 W (typical), (1.5 W, maximum) |
| TERMINAL BLOCKS | |
| Wire Size Accepted | 28 to 12 AWG |
| Pitch | 5.08 mm |
| Insulation Resistance | ≥500 MΩ @ 500 VDC |
| Maximum Torque | 5 Kg / cm |
| INDICATORS | |
| Power | Red LED |
| Data | Green LED TD, RD, CTS, RTS |
| MECHANICAL | |
| Dimensions | 13.24 x 9.29 x 3.30 cm (5.2 x 3.7 x 1.3 in) |
| Enclosure | IP30 Metal, Panel Mount (DIN rail mount option) |
| Weight | 208.65 gm (0.46 lb) |
| MEANTIME BETWEEN FAILURES (MTBF) | |
| MTBF | 194712 hours |
| MTBF Calc. Method | Parts Count Reliability Prediction |

| ENVIRONMENTAL | |
|-----------------------|---|
| Operating Temperature | -40 to +85 °C (-40 to +176 °F) |
| Storage Temperature | -40 to +85 °C (-40 to +176 °F) |
| Operating Humidity | 0 to 95%, non-condensing |
| REGULATORY | |
| Approvals | FCC, CE, UL C1/D2, File: E245458 |
| CE - Directives | 2014/30/EU Electromagnetic Compatibility Directive 2011/65/EU amended by (EU) 2015/863 Reduction of Hazardous Substances Directive (RoHS) 2012/19/EU Waste Electrical and Electronic Equipment (WEEE) |
| CE - Standards | EMC: EN 55032 - Class A Electromagnetic compatibility of multimedia equipment – Emission requirements EN 55024 - Information Technology Equipment – Immunity Characteristics – Limits and methods of measurement |
| Other | EN 55011 + AC – Information Technology Equipment – Class A RF Emissions EN 61000-6-2 – Generic Immunity Standard for (Heavy) Industrial Environments IEC 61850-3 IEEE 1613 |

MECHANICAL DIAGRAM

