

Dual Band (2.4 GHz, 5 GHz) Wi-Fi Ethernet Bridge/Router, Serial Server

AirborneM2M™ Industrial ABDN-xx-IN50xx Series

ADVANTECH

www.advantech.com



PRODUCT FEATURES

- RS-232/422/485 or 10/100 Mbps Ethernet to 802.11a/b/g/n (2.4, 5 GHz)
- Advanced Enterprise class wireless security
- One or two serial ports, one Ethernet port
- Wide operating temperature: -40 to +85 °C
- PoE 802.3af Power-over-Ethernet (Model BB-ABDN-ER-IN5018 = "PD")
- 5-36 VDC variable DC power supply (USA cord included; other cords sold separately)

AirborneM2M™ Industrial Wireless Device Serial Servers and Ethernet Bridge/Routers are built for networking equipment in a wide array of machine-to-machine (M2M) applications. AirborneM2M industrial series features industrial strength packaging and supports a wide temperature rating (-40 to +85 °C) to withstand challenging M2M environments. Available in both single and dual serial port models or a single Ethernet port model.

These AirborneM2M products establish wireless connections over both 2.4 GHz and 5 GHz bands. Whenever the 2.4 GHz airspace is overcrowded with competing wireless transmission, AirborneM2M products can be switched over to 5 GHz band to keep data flowing.

Powering Options

_External 5-36 VDC power source required. USA power cord included, other cords sold separately.

_Power-over-Ethernet (PoE) 802.3af, Powered Device (PD) (Model ABDN-ER-IN5018 only)

ORDERING INFORMATION

| MODEL NUMBER | DESCRIPTION | POE POWER-OVER-ETHERNET |
|-------------------|---|----------------------------|
| BB-ABDN-ER-IN5010 | Ethernet Bridge/Router – Industrial Wireless, Dual Band (2.4 / 5 GHz) | no |
| BB-ABDN-ER-IN5018 | Ethernet Bridge/Router, PoE (PD) – Industrial Wireless, Dual Band (2.4 / 5 GHz) | YES (PD) |
| BB-ABDN-SE-IN5410 | Serial Device Server – Industrial Wireless, Dual Band (2.4 / 5 GHz) - with one RS-232/422/485 port | no |
| BB-ABDN-SE-IN5420 | Serial Device Server – Industrial Wireless, Dual Band (2.4 / 5 GHz) - with two RS-232/422/485 ports | no |

Available in: North America, European Union (EU), Japan

ACCESSORIES - sold separately

BB-PS-WDS – 120-240 VAC, 50/60 Hz, 5 VDC, 2A barrel connector power supply (Note: includes USA cord; other cords sold separately.)

BB-MDR-20-24 – 120-240 VAC, 50/60 Hz, 24 VDC, 1.0A DIN rail power supply

BB-ACH2-DBAT-DP002 – 2dBi portable (rubber duck) 2.4GHz / 5GHz antenna

All product specifications are subject to change without notice.
ABDN-er-se-IN50xx_EthBridgeRouter-SerSvr_1819ds

ADVANTECH

orders@advantech-bb.com |
eSales@advantech-bb.com

Headquarters: 707 Dayton Rd, PO Box 1040 Ottawa, IL 61350 USA (815)433-5100 or (800)346-3119/Toll Free Fax (815)433-5104
European Office: Westlink Commercial Pk, Oranmore Co. Galway Ireland +353 91 792444 Fax +353 91 792445

Dual Band (2.4 GHz, 5 GHz) Wi-Fi Ethernet Bridge/Router, Serial Server

AirborneM2M™ Industrial ABDN-xx-IN50xx Series



SPECIFICATIONS

| TECHNOLOGY | |
|----------------------------------|--|
| Wireless Technology | IEEE 802.11 a/b/g/n, Wi-Fi Compliant |
| Wired Interface | 2 ports, RS-232/422/485, (RS-232/422 4-wire or RS-485 2-wire) 10/100 Ethernet port (Bridge, Router (NAT3) Modes) Software selectable |
| Frequency | 2.4~2.4835 GHz (US/Canada/Europe) 2.4~2.497 GHz (Japan) 5.150 ~ 5.350 GHz 5.725 ~ 5.825 GHz |
| Modulation Technology | DSSS, CCK, OFDM |
| Modulation Type | DBPSK, DQPSK, CCK, BPSK, QPSK, 16QAM, 64QAM |
| Network Access Modes | Infrastructure (Client), Ad Hoc |
| | US/Canada: 11 Channels 802.11b/g 13 Channels 802.11a Europe: 13 Channels 802.11b/g 19 Channels 802.11a France: 4 Channels 802.11b/g Japan: 14 Channels 802.11b 13 Channels 802.11g 23 Channels 802.11a |
| Wireless Data Rates | 802.11a/g = 54, 48, 36, 24, 18, 12, 9, 6 Mbps 802.11b = 11, 5.5, 2, 1 Mbps 802.11n = 65, 58.5, 42, 39, 26, 19.5, 13, 6.5 Mbps |
| Network Protocols | TCP/IP, ARP, ICMP, DHCP, DNS, UDAP, TFTP, UDP, PING, HTTP, FTP |
| Receive Sensitivity – 802.11 b/g | 54Mb/s = -72 dBm 36Mb/s = -78 dBm 18Mb/s = -84 dBm 6Mb/s = -89 dBm 11Mb/s = -86 dBm 1Mb/s = -92 dBm |
| Receive Sensitivity – 802.11 a | 54Mb/s = -74 dBm 36Mb/s = -80 dBm 6Mb/s = -90 dBm |
| Wireless Security | - Open, WEP 64 & 128 bit, WPA-PSK (TKIP), WPA2-PSK (AES), 802.1x (EAP), WPA-Enterprise, WPA2-Enterprise, EAP-TLS/MSCHAPv2, EAP-TTLS/MSCHAPv2, EAP-TTLS (MD5), EAP-PEAPv0/MSCHAPv2, LEAP - Zero host security footprint - Advanced certificate storage and management |
| Secure Communications | SSH and SSL tunneling. Encrypted configuration. |
| Transmit Power | 802.11b = 15 dBm (31.6mW) 802.11g = 12.6dBm (18.12mW) 802.11a = 17 dBm (50.1mW) |

| POWER | |
|-----------------------------------|---|
| Input Voltage | 5-36VDC +/-5%, 500mA (maximum) |
| Power Connection | 2-position terminal block, 2.1mm barrel jack |
| Power Use | 2.5W at 5VDC |
| Supply In-rush Current | 3000 mA (maximum) for 20ms |
| Source (all models) | External, required (USA cord included, other cords sold separately) |
| PoE "PD" (select model) | Power-over-Ethernet, using a 802.3af Class 1 (Model# BB-ABDN-ER-IN5018 only) |
| LED INDICATORS | |
| 4 LEDs | COMM, LINK, POWER, POST (Power on Self Test) |
| ENVIRONMENTAL | |
| Operating Temperature | -40 to +85 °C |
| Storage Temperature | -40 to +85 °C |
| Operating Humidity | 5 to 95%, non-condensing |
| MECHANICAL | |
| Antenna | RP-SMA Omni-directional 5.5 dBi 2.4GHz / 5GHz Antenna |
| Enclosure | Metal enclosure |
| Mounting | Panel mount, optional DIN rail brackets |
| Dimensions | 12.1 x 12.0 x 2.9 cm (4.9 x 4.7 x 1.2 in) |
| MEANTIME BETWEEN FAILURES (MTBF) | |
| MTBF | BB-ABDN-ER-IN5010 = 392467 hours BB-ABDN-ER-IN5018 = 377995 hours BB-ABDN-SE-IN5410 = 360740 hours BB-ABDN-SE-IN5420 = 350412 hours |
| MTBF Calc. Method | MIL 217F (Parts Count Reliability Prediction) |
| APPROVALS, DIRECTIVES & STANDARDS | |
| North America | FCC Title 47 Part 15 Class B Sub C Intentional Radiator |
| CE - Directives (Europe) | 2014/35/EU - Low Voltage Directive 2014/53/EU - Radio Equipment Directive (RED) Hereby, Advantech B+B SmartWorx declares that the radio equipment type Wi-Fi Ethernet Bridge/Router or Serial Server is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following internet address: www.advantech-bb.com 2011/65/EU - Reduction of Hazardous Substances Directive (RoHS) 2012/19/EU - Waste Electrical & Electronic Equipment Directive (WEEE) |
| CE - Standards (Europe) | EMC: ETSI EN 300 328 v2.1.1 - EMC & Radio Spectrum Matters (ERM) Wideband Transmission Systems - 2.4 GHz ISM Band ETSI EN 301 893 v2.1.1 - EMC & Radio Spectrum Matters (ERM) Wideband Transmission Systems - 5 GHz ISM Band ETSI EN 301 489-1 v2.1.1 - Applied in accordance with the specific requirements of: ETSI EN 301 489-17 v3.1.1 - EMC & Radio Spectrum Matters (ERM) Broadband Data Systems EN 55032+AC, Class A - Information Technology Equipment (ITE) - RF Emissions EN 55024 - Information Technology Equipment (ITE) - Immunity Characteristics - Limits and Methods of Measurement Safety: EN 60950-1 + A1 + A11 + A12 + A2 - Information Technology Equipment - Safety - Part 1 - General Requirements RF Exposure: EN 62311 - Assessment of electronic and electrical equipment related to human exposure restrictions for EM fields (0 Hz to 300 GHz) |