

NMC-6006FB

2 Port 100GBase-SR4 Bypass Network Mezzanine Card



Features

- 1 x Intel E830-CCAM1
- 2 ports 100GBase-SR4
- PCIe x8, Gen 5
- CE/ FCC, RoHS compliant

CE FCC




Specifications

Controller	Intel E830-CCAM1
Interface	PCIe x8, Gen5
Speed	100GbE
I/O Port	2 x MPO-MT
Reach Distance	70 /100m (OM3/OM4)
Multi Mode Fiber	Available in 50/125μm
Optical Receiver Sensitivity	-4.2 dBm
LAN LED definition	Link/Act/Bypass LED: Link: Green on Activity: Green Blinking LAN Bypass: Amber on Disconnect: Amber blinking
Advanced Software Features	Support: IEEE 802.1Q, 802.1P VLAN tags and priority IEEE 802.1Qaz (ETS) IEEE 802.1Qbb (PFC) IEEE 1588v2
OS support	Linux (CentOS, Red Hat, Ubuntu), Windows server
Operating Temperature (Air flow 0.7 m/sec)	0°C ~ 40°C (23°F~113°F) with system
Storage Temperature	-20°C ~ 65°C (-4°F~149°F)
Storage Humidity	5 ~ 85 % @ 60 °C (140 °F)
Dimension (W x H x D)	74.3 x 42.2 x 174.7 mm
Weight	0.5 kg
Certification	CE/FCC, RoHS

Ordering Information

Part Number	Description
NMC-6006FB-02A1	2 ports 100GBASE-SR4 Fiber Bypass Module

Front Panel Diagram



Dimensions

Unit: mm

