SKY-QUAD-A1000-8 SKY-QUAD-A400-4

NVIDIA RTX A1000 NVIDIA RTX A400



Features

- NVIDIA Ampere GPU architecture
- Third-generation Tensor Cores
- Second-generation RT cores
- GDDR6 memory
- AV1 Decode Support
- Max. power consumption: 50W
- Graphics bus: PCI-E 4.0 x8
- Thermal solution: Active
- Display connectors: mDP 1.4a

Introduction

With cutting-edge features and a compact form factor, the NVIDIA RTX A1000 and A400 represents NVIDIA's latest entry-level professional GPU. Built on the NVIDIA Ampere GPU architecture, this low-profile package is ideal for deployment in a wide range of small form factor workstations. These cards are equipped with the latest generation RT cores, Tensor cores, enabling generative AI, graphics, compute performance, and immersive entertainment design. Certified by a wide range of specialist applications, tested by dominant independent software vendors (ISVs) and workstation manufacturers, and supported by a global specialist team, NVIDIA RTX is the first choice for high-standard visual computing solutions in enterprise deployments.

Specifications

| Product Name | NVIDIA RTX A1000 | NVIDIA RTX A400 |
|------------------------------|---|---|
| Part Number | SKY-QUAD-A1000-8 | SKY-QUAD-A400-4 |
| GPU Memory | 8GB GDDR6 | 4GB GDDR6 |
| Memory Interface | 128-bit | 64-bit |
| Memory Bandwidth | 192 GB/s | 96 GB/s |
| NVIDIA CUDA Cores | 2,304 | 768 |
| Tensor Cores | 72 (3 rd gen) | 24 (3 rd gen) |
| RT Cores | 18 (2 nd gen) | 6 (2 nd gen) |
| Single-Precision Performance | 6.7 TFLOPS | 2.7 TFLOPS |
| System Interface | PCI Express 4.0 x8 | PCI Express 4.0 x8 |
| Max Power Consumption | 50W | 50W |
| Thermal Solution | Active | Active |
| Form Factor | 2.7 inches (H) x 6.4 inches (L), single slot, low profile | 2.7 inches (H) x 6.4 inches (L), single slot, low profile |
| Display Connectors | 4x Mini DisplayPort 1.4a with latching mechanism | 4x Mini DisplayPort 1.4a with latching mechanism |
| Max Simultaneous Displays | 4x 4096 x 2160 @ 120 Hz 4x 5120 x 2880 @ 60 Hz 2x 7680 x 4320 @ 30 Hz | 4x 4096 x 2160 @ 120 Hz 4x 5120 x 2880 @ 60 Hz 2x 7680 x 4320 @ 30 Hz |
| Graphics APIs | DirectX 12 Shader Model 6.6 OpenGL 4.6 Vulkan 1.3 | DirectX 12 Shader Model 6.6 OpenGL 4.6 Vulkan 1.3 |
| Compute APIs | CUDA, DirectCompute, OpenCL™ | CUDA, DirectCompute, OpenCL™ |
| Power Connector | - | - |
| Power Adapter Cable Included | - | - |
| Power Adapter Interface | - | - |
| Low Profile Bracket | In the accessory bag | In the accessory bag |