# SKY-QUAD-A5500-24B



## **NVIDIA RTX A5500**

#### **Features**

- NVIDIA Ampere GPU architecture
- 10,240 NVIDIA<sup>®</sup> CUDA<sup>®</sup> Cores
- 320 NVIDIA<sup>®</sup> Tensor Cores
- 80 NVIDIA<sup>®</sup> RT Cores
- 24GB GDDR6 memory with ECC
- Up to 768GB/s memory bandwidth
- Max. power consumption: 230W
- Graphics bus: PCI-E 4.0 x16
- Thermal solution: active
- Display connectors: DP 1.4a

## Introduction

With cutting-edge performance and features, the SKY-QUAD-A5500-24B (NVIDIA RTX A5500) is built on the NVIDIA Ampere GPU architecture, fulfilling the most requirements of graphics and compute-intensive tasks for designers, engineers, scientists, and artists to support their innovative solutions. The NVIDIA RTX A5500 is equipped with the latest generation RT cores, Tensor cores, and CUDA<sup>®</sup> cores for realizing AI, graphics, compute performance, and immersive entertainment design. Certified by a wide range of specialist applications, tested by dominant independent software vendors (ISVs) and workstation manufacturers, and supported by a global specialist team, NVIDIA RTX is the first choice for high-standard visual computing solutions in enterprise deployments.

## **Specifications**

| -                            |  |
|------------------------------|--|
| Product Name                 | NVIDIA RTX A5500   |
| Part Number                  | SKY-QUAD-A5500-24B   |
| GPU Memory                   | 24GB DDR6 with ECC   |
| Memory Interface             | 384-bit  |
| Memory Bandwidth             | 768 GB/s   |
| NVIDIA CUDA Cores            | 10,240   |
| Tensor Cores                 | 320  |
| RT Cores                     | 80   |
| Single-Precision Performance | 34.1 TFLOPS  |
| System Interface             | PCI Express 4.0x16   |
| Max Power Consumption        | 230W   |
| Power Connector              | 8-Pin PCle   |
| NVLink Support               | Yes, 112.5GB/s (bidirectional)   |
| Thermal Solution             | Active   |
| Form Factor                  | 4.4 inches H x<br>10.5 inches L,<br>dual slot, full height                     |
| Display Connectors           | 4 x DisplayPort 1.4a   |
| Max Simultaneous Displays    | 4 x 4096 x 2160 @ 120 Hz<br>4 x 5120 x 2880 @ 60 Hz<br>2 x 7680 x 4320 @ 60 Hz |
| Graphics APIs                | DirectX 12.07<br>Shader Model 5.17<br>OpenGL 4.68<br>Vulkan 1.2                |
| Virtualization Ready         | Yes  |
| Compute APIs                 | CUDA, DirectCompute, OpenCL™   |
|                              |  |