

SPC-815(M)/SPC-821(M) V2

All-Around IP Protection Standalone HD Base-T Monitor



Features

- 15.6"/21.5" Full HD TFT LED LCD display
- 16:9 widescreen with P-CAP multi-touch control
- Support HD Base-T long distance video streaming
- Front-facing LED indicators show operating status
- Silicone-free enclosure with all-round IP65-rated protection
- Supports CP 40 (Rittal) and CS-480 B.Flex (Bernstein) mount standards
- Supports the wide series of operational panel configuration
- Caution: SPC-ILINK MUST be order together

Introduction

SPC-800(M) V2 are Poll-mountable industrial monitors that can be can be integrated with wide series of operational panel kit. Designed to support diverse industrial mounting standards, such as CP 40 (Rittal) and CS-480 (Bernstein), SPC-800(M) V2 are series of versatile industrial monitors that can be installed in a variety of environment. The monitors are also equipped with a silicone-free enclosure that features all-around IP65-rated protection from water and dust. Moreover, with the aluminum cable housing, all cables and wiring can be hidden for a clean appearance and simplified wiring installation.

Specifications

General

- **Certification** BSMI, CE, FCC Class A, UL
- **Cooling System** Fanless design
- **Dimensions (W x H x D)** 15.6": 400.74 x 331.76 x 185mm
21.5": 545.24 x 415.59 x 185mm
- **Enclosure** Front bezel: Die-cast aluminum alloy
Rear housing: Die-cast aluminum alloy
- **Mount Options** Pole Mount (Rittal CP40 & Bernstein CS-480)
VESA Mount (Optional through VESA Kit)
- **Power Input** 19-24 V_{DC}
- **Weight (Net)** 15.6": 6KG
21.5": 8KG
- **Video Input** HD Base-T Ethernet (RJ45) Input
- **Video Output** HD Base-T Ethernet (RJ45) Output (SKU Optional)
- **I/O** 4 x USB 2.0

LCD Display

- **Display Type** Full HD TFT LED
- **Display Size** 15.6" / 21.5"
- **Max. Resolution** 15.6": 1920 x 1080
21.5": 1920 x 1080
- **Max. Colors** 16.7 M
- **Luminance** 15.6": 400 nits
21.5": 250 nits
- **Viewing Angle (H/V)** 15.6": 170°/130°
21.5": 178°/178°
- **Backlight** 50,000 hr lifetime

Touchscreen

- **Light Transmission** ≥88%
- **Resolution** 4096 x 4096 dots
- **Type** Projected capacitive

Environment

- **Humidity** 95% RH @ 40 °C/104 °F, non-condensing
- **Ingress Protection** All-Around IP65
- **Operating Temperature** 0 ~ 55 °C (32 ~ 131 °F)
- **Storage Temperature** -20 ~ 60 °C (-4 ~ 140 °F)

Modular Ordering Information

Note: System Unit, Operational Panel Kit and ILINK Transmitter Module should be ordered together

System Unit

- **SPC-815-MA** IP65-rated standalone monitor with 15.6" FHD, P-CAP touch, HD Base-T
- **SPC-815-MB** IP65-rated standalone monitor with 15.6" FHD, P-CAP touch, HD Base-T, Daisy Chain Capability
- **SPC-821-MA** IP65-rated standalone monitor with 21.5" FHD, P-CAP touch, HD Base-T
- **SPC-821-MB** IP65-rated standalone monitor with 21.5" FHD, P-CAP touch, HD Base-T, Daisy Chain Capability

ILINK Module Unit*

- **SPC-ILINK-TX** Standalone ILINK Transmitter, HD Base-T Wall Mount module
- **SPC-ILINK-RX** Standalone ILINK Receiver, HD Base-T Wall Mount module


*For more information on SPC-ILINK module, please refer to the dedicated data-sheet

SPC-815(M)/SPC-821(M) V2


Dimensions

Unit: mm [inch]

SPC-815(M)



SPC-821(M)



Operational Panel Kit

- **SPC-815-OPKA** 15.6" operational panel kit, 1 x Front Extended USB Port
- **SPC-815-OPKB** 15.6" operational panel kit, 1 x E-Stop, 1 x Red Push Button, 1 x Green Push Button, 1 x Blue Push Button, 1 x Key Selector, 1 x Front Extended USB Port
- **SPC-815-OPKC** 15.6" operational panel kit, 1 x E-Stop, 1 x Red Push Button, 1 x Green Push Button, 1 x Blue Push Button, 1 x Key Selector, 1 x Front Extended USB Port, 1 x RFID Antenna*
- **SPC-821-OPKA** 21.5" operational panel kit, 1 x Front Extended USB Port
- **SPC-821-OPKB** 21.5" operational panel kit, 1 x E-Stop, 1 x Red Push Button, 1 x Green Push Button, 1 x Blue Push Button, 1 x Key Selector, 1 x Front Extended USB Port
- **SPC-821-OPKC** 21.5" operational panel kit, 1 x E-Stop, 1 x Red Push Button, 1 x Green Push Button, 1 x Blue Push Button, 1 x Key Selector, 1 x Front Extended USB Port, 1 x RFID Antenna*

Optional Accessories

- **1702002600** Power cable US plug 1.8 M
- **1702002605** Power cable EU plug 1.8 M
- **1702031801** Power cable UK plug 1.8 M
- **1700000596** Power cable China plug 1.8 M
- **1700036187-01** Certified Cat-6A S/FTP RJ45 Cable 300cm
- **1700036188-01** Certified Cat-6A S/FTP RJ45 Cable 1500cm
- **1700036189-01** Certified Cat-6A S/FTP RJ45 Cable 5000cm
- **1700036190-01** Certified Cat-6A S/FTP RJ45 Cable 7000cm
- **98R1800M010** VESA Kit for SPC-800 V2
- **96PSA-A60W24T2-3** 60W 24V_{DC} power supply

*NRE for RF Certification may be required, please contact local sales for additional detail.

Packing List

Item	Part No.	Depiction	Qty
Plug-In Block	1652002205	Plug-In Block 1x3P/5.08mm/PA66/F/VA/Sn/GR/H15	1
Grounding cable	1703011001-11	A Cable G-TEM 4.3 100CM C=GR/Y	1
Grounding screw	1935130610	Screw M3x6L R/S(TW) D=5.5 H=2 (2+) ST BIZn	1
Flange	9651800M000	Accessory Kit for SPC-800 (M) PIPE Mounting	1