

# Environment Data Collector



CE FC

## Features

- Lightweight gateways with software for uploading data from the edge to the cloud
- Supports communication with 200+ PLCs and I/O modules
- Equipment data integrated into middleware with secure data conversion
- Data backups to a database and FTP server
- Supports various different I/O ports such as serial, Ethernet, AI and DI/O
- Supports wireless interface for remote connectivity

## Introduction

For facility monitoring, distributed solar power, smart factory and cloud based applications, which require total wireless and Ethernet communication solutions, Advantech released the SRP-IFS210-D36TAE, SRP-IFS420-E12TAE, SRP-IFS420-E14TAE and SRP-IFS420-E16TAE industrial communication gateways. SRP series gateways have an open platform design with Cortex A8 processor, two 10/100 Ethernet ports and operating temperature ranges of -40~70°C. With a Linux operating system and open WISE-Edgelink SDK, system integrators can easily develop applications which precisely fit their need.

## Features

### Data storage and transmission

SRP-IFS210-D36TAE, SRP-IFS420-E12TAE, SRP-IFS420-E14TAE and SRP-IFS420-E16TAE integrates local data storage and forwarding to ensure all useful information will be captured whenever the network is down to help reduce equipment maintenance costs.

### Advanced metering infrastructure (AMI) tracks power consumption and predicts demand

AMI expands the range of time-based programs that can be offered to consumers. Smart systems such as Energy Management can make it easier for consumers to change behaviors and reduce peak periods of power consumption.

### Improved maintenance efficiency via remote monitoring

With WISE-EdgeLink, SRP-IFS210-D36TAE, SRP-IFS420-E12TAE, SRP-IFS420-E14TAE and SRP-IFS420-E16TAE support a wide range of power equipment protocols, energy meters, and HVAC devices. Real-time operation and power distribution status can be synchronized to help meet energy efficiency targets.

### Platform scalability with distributed management and multi service access

Unlike virtual machine access, SRP-IFS210-D36TAE, SRP-IFS420-E12TAE, SRP-IFS420-E14TAE and SRP-IFS420-E16TAE support data access to a variety of cloud platforms through the standard MQTT protocol, with distributed access control architecture for different environments.

## Environment Data Collector

### Specifications

|                       |                     |                                                                                       |                                                                        |                             |                                   |
|-----------------------|---------------------|---------------------------------------------------------------------------------------|------------------------------------------------------------------------|-----------------------------|-----------------------------------|
| Part Number           |                     | SRP-IFS210-D36TAE                                                                     | SRP-IFS420-E12TAE                                                      | SRP-IFS420-E14TAE           | SRP-IFS420-E16TAE                 |
| Hardware Platform     |                     | ADAM-3600<br>ADAM-3651                                                                | ECU-1051                                                               | ECU-1251                    | ECU-1152                          |
| CPU                   |                     | Cortex-A8, 600MHz                                                                     | Cortex-A8, 600MHz                                                      | Cortex-A8, 800MHz           | Cortex-A8, 800MHz                 |
| Memory                |                     | DDR3L 256MB                                                                           | DDR3L 256MB                                                            | DDR3L 256MB                 | DDR3L 512MB                       |
| Storage               |                     | 1GB SD card                                                                           | 1GB SD card                                                            | 1GB SD card                 | 1GB SD card                       |
| Serial Port           |                     | 1 x RS232/485- DB9<br>2 x RS485- Terminal Block                                       | 2 x RS-232/485                                                         | 4 x RS-232/485              | 6 x RS-232/485                    |
| Communication         | Ethernet Port       |                                                                                       | 2 x 10/100 Base-T RJ-45 ports                                          |                             |                                   |
|                       | USB Port            | 1 x USB2.0                                                                            | N/A*                                                                   | 1 x USB2.0                  | 1 x USB2.0                        |
|                       | Wireless (Optional) |                                                                                       | Interface: 1x Mini-PCle (Full-size) Type: WIFI/Cellular/4G Signal: USB |                             |                                   |
|                       | DI/DO/AI/AO         | 8AI / 16DI / 4DO                                                                      | N/A*                                                                   | N/A*                        | N/A*                              |
| Software              | Operating System    | RT-Linux 3.12                                                                         | RT-Linux 3.12                                                          | RT-Linux 3.12               | RT-Linux 3.12                     |
|                       | Configuration Tool  | Advantech WISE-EdgeLink Studio                                                        |                                                                        |                             |                                   |
|                       | Protocol Support    | IEC-60870-101(master)/ 104(slave),<br>Modbus/TCP, DNP3 L2, TCP/IP, DHCP, IEC104, MQTT |                                                                        |                             |                                   |
|                       | Programming         | IEC-61131-3, Linux C, Python, Node-RED, Restful API, Web service API                  |                                                                        |                             |                                   |
| Certifications        |                     | CE/FCC<br>(No RED certification)                                                      | CE, FCC<br>(No RED certification)                                      | CE, FCC<br>(RED compliance) | CE, FCC<br>(No RED certification) |
| Power Requirements    |                     | 10 ~ 30 V <sub>DC</sub>                                                               | 10 ~ 30 V <sub>DC</sub>                                                | 10 ~ 30 V <sub>DC</sub>     | 10 ~ 30 V <sub>DC</sub>           |
| Operating Temperature |                     | -40 ~ 70°C                                                                            | -40 ~ 70°C                                                             | -40 ~ 70°C                  | -40 ~ 70°C                        |

Legend: N/A = Not Applicable

### Ordering Information

| Part Number       | Description                                                                                                          |
|-------------------|----------------------------------------------------------------------------------------------------------------------|
| SRP-IFS210-D36TAE | Modular edge intelligent data acquisition with WISE-EdgeLink, 2 x LAN, 3 x COM, 8 x AI, 16 x DI, 4 x DO, 1GB storage |
| SRP-IFS420-E12TAE | Protocol gateway with WISE-EdgeLink, 2xLAN, 2xCOM, 1GB storage                                                       |
| SRP-IFS420-E14TAE | Protocol gateway with WISE-EdgeLink, 2xLAN, 4xCOM, 1GB storage                                                       |
| SRP-IFS420-E16TAE | Protocol gateway with WISE-EdgeLink, 2xLAN, 6xCOM, 1GB storage                                                       |