


VUE-4156

15.6" AIO Touch Computer



Features


- 15.6" active screen size
- Built-in Rockchip RK3566 and OS Android 11
- 6-axis color adjustment (Green/Red/Blue/Cyan/Magenta/Yellow) for high level and more accuracy customized image
- Full-flat cover glass for extremely simple and elegant surface design
- Adopts industrial-grade components for guaranteed performance
- Mount with multi-way and easy to extend peripheral devices (box PC/camera...)
- Front IP65 water-proof rating and IK08 high-level impact protection
- Support 10-point touch function (PCAP technology)
- Excellent noise immunity well-suited for rugged applications (CS 10V)
- Support many touch method including fingers, glove, and stylus

Specifications

System	CPU	Rockchip RK3566		
	Memory	4GB LPDDR4		
	Storage	128GB eMMC		
	Ethernet	LAN port x 1		
OS Support	OS version	Android 11		
	Control Method	OSD button (ON/OFF, LEFT, RIGHT, MENU, AUTO)		
	OSD Function	Luminance (Brightness, Contrast, Eco Mode, DCR) , Image Setup (Clock, Focus, H/V Position, Image Ratio), Color Temperature (Warm, Normal, Cool, sRGB, Red, Green, Blue), OSD Setup (H Position, V Position, Timeout, Language), Extra (Input select, DDCD/CI, Reset, Information)		
	OSD Language	Simplified Chinese, Traditional Chinese, English, Korea, French, Spanish, Russian, Portuguese		
Display	Active Screen Size	15.6 inch		
	Resolution	1920 x 1080 (FHD)		
	Brightness	450 nits (LCM panel, typ.)		
	Contrast Ratio	800:1 (Typ.)		
	Aspect Ratio	16:9		
	Viewing Angle	89° / 89° / 89° / 89°		
	Response Time	25 ms (Typ.)		
	Backlight Life (hours)	50,000 (Typ.)		
Touch	Touch Type	Projected Capacitive Touch (PCAP)		
	Touch Function	10 points		
	Touch Interface	USB		
Connectivity	Input Video	HDMI 1.4 x 1 (HDCP 1.4)		
	Input Audio	N/A		
	Input Control	RS-232 input		
	Input Other slots/ports	USB2.0 Host x2 (internal), USB3.0 Type A x3 (5V, 1A)		
	Output Video	N/A		
	Output Audio	2W+2W Internal Speaker		
	Output Control	N/A		
Power	Power Type	External Adaptor 12V~19V 65 W		
	Power Input	100-240V _{AC} , 50-60Hz		
	Power Consumption	24W		
Environment	Operating	Temperature	0°C- +40°C	
		Humidity	30% to 80% (non-condensing)	
	Storage	Temperature	-10°C- +60°C	
		Humidity	10% to 80% (non-condensing)	
Mechanical Specification	Housing Material	1.0 mm sheet metal (Black)		
	VESA Compatibility	100 x 100 mm		
	Dimensions (W x H x D)	Physical	384.80 x 237.10 x 49.04 mm	
		Packing	455 x 330 x 185 mm	
	Weight	Net	2.9 kg	
		Gross	4.5 Kg	
Installation	Mounting on a wall/machine	100 x 100 mm, VESA grid		
	Mounting with stand/arm	100 x 100 mm, VESA grid		
	Mounting through bracket	64 mm, Side mount screw hole		
Approbation	Certificates	IEC/EN 60950+62368, UL62368, BSMI, CE, FCC, UKCA		
Warranty		2-year (1-year for panel)		

Dimensions

Unit: mm [inch]



Ordering Information

Part Number	Description	Packing List
VUE-4156-FD45PA-N4	Advantech 15.6" All-in-One PC (incl. Japan, Korean, Australia, and Middle East Power Cord)	<ul style="list-style-type: none"> ▪ Power Cord (1.5M, Black) ▪ Power Adaptor (1.5M, Black) ▪ HDMI Cable (1.5M, Black) ▪ Side Mount Bracket kit ▪ Startup Manual (Paper)
VUE-4156-FD45PC-N4	Advantech 15.6" All-in-One PC (incl. China Power Cord)	
VUE-4156-FD45PX-N4	Advantech 15.6" All-in-One PC (incl. Taiwan, US, Europe, and England Power Cord)	

Optional Accessories

Part Number	Description
960T-A15DEE-B0	Active Stylus Pen for VUE-4000 series, Black
960T-SD-10H10-L	Desktop Stand for VUE-4000, VESA100x100, Large, support up to 7kg