



ALL-IN-ONE



MOBILITY



KIOSK



PANELS PC



PRINTERS



DISPLAYS



ACCESSORIES

ADVANTECH

AURES

YUNO II

ASC-415 SERIES

Universal multi-configuration integrated system

Robust, yet compact
and stylish POS system

YUNO II is a new generation of the YUNO POS system ; robust, stylish and compact, it suits the many applications of the POS vertical sectors.

A fanless, flexible and high-performance hardware, it offers a choice between 5 different INTEL platforms (11th Gen Elkhart Late & Tiger Lake, 12th Gen Twin Lake); the system is available in 2 formats (traditional 4:3 15" screen and Wide 16:9 15.6" screen with Full HD) and equipped with a shock- and scratch-proof, multi-touch, projected, capacitive screen (10 point PCAP technology).


Very flexible, YUNO II is available with VESA fixings options (for wall or pole mounted solutions).

The standard version features a NVMe-M.2 flash disk and stands up to dirt in the toughest settings (fat, crumbs, dust, splashes and leftovers in kitchens, restaurants and bakeries). It integrates energy efficient processors (J6412, or i3-1115G4E, or i5-1145G7E as well as the latest N150 and



3-N355) and a heat-dissipating aluminium structure, ensuring compliance with environmental standards (low carbon footprint).

YUNO II is an accessible product whose many features (technology, ergonomics, flexibility and design) make it good value for money. It constitutes a sensible, cost effective and long-term POS IT investment.



YUNO II



- 11th generation of INTEL processors (J6412, i3-1115G4E, i5-1145G7E)
- 12th generation of INTEL processors (N150, 3-N355)
(Energy efficient processors for low carbon footprint)
- NVMe.M2 2 slots
- Projected, capacitive, multi-touch screen (10 point - PCAP)
- 4:3 or 16:9 formats (15" or 15.6")
- RAM 8 GB (standard) - up to 32 GB on 11th Gen; up to 16 GB on 12th Gen
- Tilting base: 0-90°
- Discreet yet easily accessible connectivity
- 2nd screen output
- Available with VESA bracket option, for wall and pole mounted installations
- Thinner base for a light design
- Detachable magnetic rear cover (easy and quick to remove/replace)
- Transparent status LED lighted AURES logo on the left side of the base (green / amber)
- Easy maintenance (the most compact motherboard in the market)
- 2 LAN port (1 LAN port on model with J6412 processor)



MODEL	YUNO II
Processor(s)	INTEL Elkhart Lake J6412, Tiger Lake i3-1115G4E or i5-1145G7E (fanless) INTEL Twin Lake N150 or 3-N355 (fanless)
RAM	DDR4 - 8GB standard (up to 32GB) for 11 th Gen DDR5 - 8GB standard (up to 16GB) for 12 th Gen Slot 1: M2.2280 PCIe3.0 (NVMe) 256GB - standard SATA supported for 11 th Gen CPUs Slot 2: M2.2280 PCIe3.0 (NVMe)
LCD	15" TFT (1024 x 768) or 15.6" (1920 x 1080) (wide format in full HD) LED back-lighting
Touchscreen	Flat, zero bezel & multi-touch screen with projected, capacitive panel (10 point PCAP)
Brightness	400 cd/m ²

INPUT-OUTPUT PORTS	
Serial	2 x serial ports (RJ50 connector)
USB	6 x USB 3.0 2 x USB-C (1 to CPU)
LAN	2 x 10/100/1000Base-T (1 x LAN for J6412 model)
External display	Port with support for HDMI, DVI and VGA (via USB-C)
Cash Drawer	24/12 V DC
Audio	Internal loudspeaker
Power Supply	external 19v. DC
TPM2.0	on all boards

MISCELLANEOUS	
EMI	CE/FCC Class B, UL, RCM
VPRO	on I5 version
Operating Temperature	0-35 °C
Front	Dust- and splash-proof
Colour	Black (grey base)
Materials	Polycarbonate (cover) + aluminium (structure)
MTBF (screen)	50,000 hours
Dimensions (W x D x H)	342.9 x 167.5 x 303.8 mm (15" format, with vertical screen) 382 x 170.5 x 276.1 mm (15.6" Wide format, screen vertical)
Weight	5.5 - 6.5 kg depending on the option (15" format) 6.5 - 7.5 kg (15.6" Wide format)
Compatible OS	Windows 10 IoT, Windows 11 IoT LTSC 2024, Linux

OPTIONAL EXTRAS	
Multi-Technology Card Reader	for combined reading of MSR and RFID (high and low frequencies), Bluetooth (BLE), NFC...
Addimat and/or Dallas readers	1 slot, at right of EPOS terminal
Barcode scanners	2D
Fingerprint reader	Yes
Customer display	20 characters x 2 lines LCM
2 nd screen (touch or non touch)	10.1" - 16:9 1280 x 800 Flat LED screen
WIFI	via BT/Wi-Fi USB key
VESA fixings option(s)	Optional brackets
Anti-glare touch screen	
White Cover	